



CONSTRUCTION LEVELERS

With the largest drag capacity on the market, K-Tec Land Levelers help contractors score a perfect grade on construction haul roads and land leveling projects. Our lineup of construction levelers helps you to keep a smooth haul road which allows for faster cycle times and less structural damage to your equipment. Ranging from 14' to 20' / 4.2m to 6m in width and with the ability to drag between 11 - 16 cubic yards / 8.4 - 12.2 cubic metres, these effective earthmovers save you time and money.



K-TEC CONSTRUCTION LEVELER FEATURES

								1 YEAR STRUCTURAL 6 MONTH PARTS & LABOR
14-20' WIDTH	ADAPTABLE GPS LASER	TURNING RADIUS 90°	PRECISION DEPTH LEVEL GAUGE	SIMPLISTIC TILT	MECHANICAL SLOPE METER	FOLDABLE HITCH ROAD TRANSPORT	SHIPPING	WARRANTY

CONSTRUCTION LEVELER SPECIFICATIONS

MODEL	BUCKET DIMENSIONS		CAPACITY		CUTTING WIDTH	
	Standard	Metric	Standard	Metric	Standard	Metric
1411 Flex	14' W x 5' 1" H x 4' 7" L	4.26m W x 1.5m H x 1.4m L	11.4 Cubic Yards	8.7 Cubic Metres	14'	4.26m
1613 Flex	16' W x 5' 1" H x 4' 7" L	4.9m W x 1.5m H x 1.4m L	13 Cubic Yards	10 Cubic Metres	16'	4.9m
1814 Flex	18' W x 5' 1" H x 4' 7" L	5.4m W x 1.5m H x 1.4m L	14.6 Cubic Yards	11.1 Cubic Metres	18'	5.5m
2016 Flex	20' W x 5' 1" H x 4' 7" L	6.1m W x 1.5m H x 1.4m L	16.3 Cubic Yards	12.5 Cubic Metres	20'	6.1m

STANDARD FEATURES
Single Simplistic Tilt
Depth Level Gauge
Mechanical Slope Meter
GPS/Laser Adaptability
385/65 R22.5 x 4 Tires

TRANSPORT DIMENSIONS

MODEL	OVERALL WIDTH & LENGTH		SHIPPING WEIGHT		FOLDED DIMENSIONS	
	Standard	Metric	Standard	Metric	Standard	Metric
1411 Flex	14' 3" W x 25' L	4.34m W x 7.62m L	10,135 lbs	10,135 lbs	8' 6" W x 10' 6" H x 22' L	2.59m W x 3.2m H x 6.7m L
1613 Flex	16' 3" W x 25' L	4.95m W x 7.62m L	10,600 lbs	4,808 kgs	8' 6" W x 10' 6" H x 23' L	2.59m W x 3.2m H x 7.0m L
1814 Flex	18' 3" W x 25' L	5.56m W x 7.62m L	11,065 lbs	5,019 kgs	8' 6" W x 10' 6" H x 24' L	2.59m W x 3.2m H x 7.31m L
2016 Flex	20' 3" W x 25' L	6.17m W x 7.62m L	11,530 lbs	5,230 kgs	8' 6" W x 10' 6" H x 25' L	2.59m W x 3.2m H x 7.62m L

OPTIONAL FEATURES
LED Lights
Rear Hitch

HYDRAULIC CONFIGURATIONS
1/2" Tips
3/4" Tips

RECOMMENDED POWER UNITS

Utility Tractor

1411 Flex - 1613 Flex
250HP +/-186 KW +

Agricultural Tractor

1814 Flex - 2016 Flex
350HP +/-260 KW +

BLADE CONFIGURATIONS

	8" (203mm) Curved Grader Blade
	Straight Flat Cutting Edge
	Serrated Cutting Edge

Specifications are subject to change without notice.

